

77 CD Player

Features

- Bus powered or AC mains powered.
- AC Mains powered unit has conventional phono outputs.
- AC mains powered comes with own standard remote control.
- Both units are operated from front panel or from the 77 system console for more sophisticated controls.
- The 77CD uses the same highly acclaimed Delta Sigma digital to analogue conversion system as the 67CD.



Specifications

| | |
|---------------------------|--|
| Operation | Full function by Quad's two way infrared remote control or operation from front panel push-buttons (applies to both CD versions) |
| Number of channels | Two |
| Frequency response | < +/-0.1dB 20-20 KHz |
| Phase Linearity | < +/-0.5 20-20 KHz |
| Signal/Noise Ratio | >100dB 20-20 KHz |
| Cross-talk | >100dB at 1 KHz |
| Total Harmonic Distortion | <0.002% at 1 KHz |
| Wow and Flutter | below measurement level |
| D/A Conversion | 18 bit 64X oversampling Delta Sigma Converter |
| Audio Output | 2V rms max. 300mV on normal programme material |
| Mains Voltage | 110-120V or 200-240V 50-60Hz; see rating plate of player back |
| Power Consumption | 14w approximately |
| Dimensions | 321mm wide; 65mm high; 300mm deep |
| Weight | 3.5kg approximately |